Certificate Number Report Reference Date	UL-US-L467465-111-13704102-3 E467465-20140731 26-Oct-2022
Issued to:	Suzhou Inovance Technology Co Ltd 16 Youxiang Rd Yuexi Town Wuzhong District Suzhou, Jiangsu 215104 China
This is to certify that epresentative samples of	NMMS - Power Conversion Equipment See Addendum Page for Product Designation(s).
	Have been evaluated by UL in accordance with the Standard(s) indicated on this Certificate.
Standard(s) for Safety:	UL 61800-5-1, 1st Ed., Issue Date: 2012-06-08, Revision Date: 2021-02-11
Additional Information:	See the UL Online Certifications Directory at https://iq.ulprospector.com for additional information

This Certificate of Compliance indicates that representative samples of the product described in the certification report have met the requirements for UL certification. It does not provide authorization to apply the UL Mark. Only the Authorization Page that references the Follow-Up Services Procedure for ongoing surveillance provides authorization to apply the UL Mark.

Only those products bearing the UL Mark should be considered as being UL Certified and covered under UL's Follow-Up Services.

Look for the UL Certification Mark on the product.

X 4 mill Bruce Mahre

Bruce Mahrenholz, Director North American Certification Program

re

Certificate Number Report Reference Date

UL-US-L467465-111-13704102-3 E467465-20140731 26-Oct-2022

This is to certify that representative samples of the product as specified on this certificate were tested according to the current UL requirements

Model	Category Description	
CS600 followed by -D, followed by 300, 400 followed by A, may be followed by any alphanumeric suffixes.	Power Conversion Equipment	
MD520, Enclosed type 1 MD520, followed by -4T, followed by 18.5, 22, 30, 37, 45, 55, 75, 90 and 110, followed by B or null, followed by S or null, followed by -T or null, followed by -P1, may be followed by any alphanumeric suffixes.	Power Conversion Equipment	
Enclosed Type 1 Power Conversion Equipment,, Cat. MD500 follow by T, followed by 18.5, 22, 30, 37, 45, 55, 75, 90 and 110, followed by G, follow by / or null , follow by 22, 30, 37, 45, 55, 75, 90, 110 and 132 or null, followed by P or null, follow by B or null, follow by -T or null, follow by - PLUS, follow by – P1, may be followed by any alphanumeric suffixes. Open Type Power Conversion Equipment, Cat. MD500 follow by T, followed by 18.5, 22, 30, 37, 45, 55, 75, 90 and 110, followed by G, follow by / or null, follow by 22, 30, 37, 45, 55, 75, 90, 110 and 132 or null, followed by P or null, follow by B or null, follow by -T or null, follow by – PLUS, may be followed by any alphanumeric suffixes.	Power Conversion Equipment	
Enclosed Type 1, Models CS200,, CS710 followed by - 4T, followed by 18.5, 22, 30, 37, 45, 55, 75, 90 and 110, followed by G, may be followed by B or null, followed by -P1, may be followed by any alphanumeric suffixes.	Power Conversion Equipment	
Enclosed Type 1, Models IS580,, followed by T, followed by 020, 030, 035, 040, 050, 070, 080, 100, 140, 170 or 210, followed by -R1, -R2, or -D, followed by -P1, may be followed by any alphanumeric suffixes.	Power Conversion Equipment	
Enclosed Type 1, Models MD290,, followed by T, followed by 18.5, 22, 30, 37, 45, 55, 75, 90, 110 or 132, followed by G, followed by /, followed by 22, 30, 37, 45, 55, 75, 90, 110 or 132, followed by P, followed by B or null, followed by –P1, may be followed by any alphanumeric suffixes.	Power Conversion Equipment	
Enclosed Type 1, Models MD500,, MD500E, followed by T, followed by 18.5, 22, 30, 37, 45, 55, 75, 90, 110 and 132, followed by P or G, may be followed by B or null,	Power Conversion Equipment	

Barnelly

Bruce Mahrenholz, Director North American Certification Program

UL LLC

### Certificate Number Report Reference Date

UL-US-L467465-111-13704102-3 E467465-20140731 26-Oct-2022

followed by -P1, may be followed by any alphanumeric suffixes.	
MD520-2T, Models MD520, followed by -2T, followed by 11, 15, 18.5, 22, 30, 37, 45 and 55, followed by B or null, followed by S or null, followed by -T or null, followed by null, may be followed by any alphanumeric suffixes.	Power Conversion Equipment
MD520-2T-P1, Models MD520, followed by -2T, followed by 11, 15, 18.5, 22, 30, 37, 45 and 55, followed by B or null, followed by S or null, followed by -T or null, followed by -P1, may be followed by any alphanumeric suffixes.	Power Conversion Equipment
<b>T5-T8</b> , Models CS200, CS710, followed by -4T, followed by 18.5, 22, 30, 37, 45, 55, 75, 90 and 110, followed by G, may be followed by B or null, followed by -P1, may be followed by any alphanumeric suffixes.	AC DRIVE
<b>T5-T8</b> , Models IS580, followed by T, followed by 020, 030, 035, 040, 050, 070, 080, 100, 140, 170 or 210, followed by -R1, -R2, or -D, followed by -P1, may be followed by any alphanumeric suffixes.	AC DRIVE
<b>T5-T8</b> , Models MD290, followed by T, followed by 18.5, 22, 30, 37, 45, 55, 75, 90, 110 or 132, followed by G, followed by /, followed by 22, 30, 37, 45, 55, 75, 90, 110 or 132, followed by P, followed by B or null, followed by - P1, may be followed by any alphanumeric suffixes.	AC DRIVE
<b>T5-T8</b> , Models MD500, MD500E, followed by T, followed by 18.5, 22, 30, 37, 45, 55, 75, 90, 110 and 132, followed by P or G, may be followed by B or null, followed by -P1, may be followed by any alphanumeric suffixes.	AC DRIVE
<b>MD520</b> , Open type MD520, followed by -4T, followed by 18.5, 22, 30, 37, 45, 55, 75, 90 and 110, followed by B or null, followed by S or null, followed by -T or null, followed by null, may be followed by any alphanumeric suffixes.	Power Conversion Equipment
Open type, Models CS200,, CS710 followed by -4T, followed by 18.5, 22, 30, 37, 45, 55, 75, 90 and 110, followed by G, may be followed by B or null, may be followed by any alphanumeric suffixes.	Power Conversion Equipment
Open type, Models MD290,, followed by T, followed by 18.5, 22, 30, 37, 45, 55, 75, 90, 110 or 132, followed by G, followed by /, followed by 22, 30, 37, 45, 55, 75, 90, 110 or 132, followed by P, followed by B or null, may be followed by any alphanumeric suffixes.	Power Conversion Equipment
Open type, Models MD500,, MD500E, followed by T, followed by 18.5, 22, 30, 37, 45, 55, 75, 90, 110 and 132, followed by P or G, may be followed by B or null, may be followed by any alphanumeric suffixes.	Power Conversion Equipment

Bamely

Bruce Mahrenholz, Director North American Certification Program

UL LLC

Certificate Number Report Reference Date

UL-US-L467465-111-13704102-3 E467465-20140731 26-Oct-2022

Open type, Models IS580,, followed by T, followed by	Power Conversion Equipment
020, 030, 035, 040, 050, 070, 080, 100, 140, 170 or 210,	Ur XUr XUr XUr XUr X
followed by -R1, -R2, or -D, may be followed by any	いいいいいいい
alphanumeric suffixes.	$\times \times \times \times \times$

Bamely

Bruce Mahrenholz, Director North American Certification Program

UL LLC



Certificate Number Report Reference Date	UL-CA-L467465-411-13704102-3 E467465-20140731 26-Oct-2022
Issued to:	Suzhou Inovance Technology Co Ltd 16 Youxiang Rd Yuexi Town Wuzhong District Suzhou, Jiangsu 215104 China
This is to certify that representative samples of	NMMS7 - Power Conversion Equipment Certified for Canada See Addendum Page for Product Designation(s).
	Have been evaluated by UL in accordance with the Standard(s) indicated on this Certificate.
Standard(s) for Safety:	CSA C22.2 No. 274, 2nd Ed., Issue Date: 2017-04-01
Additional Information:	See the UL Online Certifications Directory at <a href="https://iq.ulprospector.com">https://iq.ulprospector.com</a> for additional information

This Certificate of Compliance indicates that representative samples of the product described in the certification report have met the requirements for UL certification. It does not provide authorization to apply the UL Mark. Only the Authorization Page that references the Follow-Up Services Procedure for ongoing surveillance provides authorization to apply the UL Mark.

Only those products bearing the UL Mark should be considered as being UL Certified and covered under UL's Follow-Up Services.

Look for the UL Certification Mark on the product.

+ mally ĸ

Bruce Mahrenholz, Director North American Certification Program

Certificate Number Report Reference Date

UL-CA-L467465-411-13704102-3 E467465-20140731 26-Oct-2022

This is to certify that representative samples of the product as specified on this certificate were tested according to the current UL requirements

Model	Category Description	
CS600 followed by -D, followed by 300, 400 followed by A, may be followed by any alphanumeric suffixes.	Power Conversion Equipment	
MD520, Enclosed type 1 MD520, followed by -4T, followed by 18.5, 22, 30, 37, 45, 55, 75, 90 and 110, followed by B or null, followed by S or null, followed by -T or null, followed by -P1, may be followed by any alphanumeric suffixes.	Power Conversion Equipment	
Enclosed Type 1 Power Conversion Equipment,, Cat. MD500 follow by T, followed by 18.5, 22, 30, 37, 45, 55, 75, 90 and 110, followed by G, follow by / or null , follow by 22, 30, 37, 45, 55, 75, 90, 110 and 132 or null, followed by P or null, follow by B or null, follow by -T or null, follow by - PLUS, follow by – P1, may be followed by any alphanumeric suffixes. Open Type Power Conversion Equipment, Cat. MD500 follow by T, followed by 18.5, 22, 30, 37, 45, 55, 75, 90 and 110, followed by G, follow by / or null , follow by 22, 30, 37, 45, 55, 75, 90, 110 and 132 or null, followed by P or null, follow by B or null, follow by -T or null, follow by – PLUS, may be followed by any alphanumeric suffixes.	Power Conversion Equipment	
Enclosed Type 1, Models CS200,, CS710 followed by - 4T, followed by 18.5, 22, 30, 37, 45, 55, 75, 90 and 110, followed by G, may be followed by B or null, followed by -P1, may be followed by any alphanumeric suffixes.	Power Conversion Equipment	
Enclosed Type 1, Models IS580,, followed by T, followed by 020, 030, 035, 040, 050, 070, 080, 100, 140, 170 or 210, followed by -R1, -R2, or -D, followed by -P1, may be followed by any alphanumeric suffixes.	Power Conversion Equipment	
Enclosed Type 1, Models MD290,, followed by T, followed by 18.5, 22, 30, 37, 45, 55, 75, 90, 110 or 132, followed by G, followed by /, followed by 22, 30, 37, 45, 55, 75, 90, 110 or 132, followed by P, followed by B or null, followed by –P1, may be followed by any alphanumeric suffixes.	Power Conversion Equipment	
Enclosed Type 1, Models MD500, MD500E, followed by T, followed by 18.5, 22, 30, 37, 45, 55, 75, 90, 110 and 132, followed by P or G, may be followed by B or null,	Power Conversion Equipment	

Barnelly

Bruce Mahrenholz, Director North American Certification Program

UL LLC

### Certificate Number Report Reference Date

UL-CA-L467465-411-13704102-3 E467465-20140731 26-Oct-2022

followed by -P1, may be followed by any alphanumeric suffixes.	
MD520-2T, Models MD520, followed by -2T, followed by 11, 15, 18.5, 22, 30, 37, 45 and 55, followed by B or null,	Power Conversion Equipment
followed by S or null, followed by -T or null, followed by	
null, may be followed by any alphanumeric suffixes.	Dewer Conversion Equipment
MD520-2T-P1, Models MD520, followed by -2T, followed by 11, 15, 18.5, 22, 30, 37, 45 and 55, followed by B or null, followed by S or null, followed by -T or null, followed by -P1, may be followed by any alphanumeric suffixes.	Power Conversion Equipment
<b>T5-T8</b> , Models CS200, CS710, followed by -4T, followed by 18.5, 22, 30, 37, 45, 55, 75, 90 and 110, followed by G, may be followed by B or null, followed by -P1, may be followed by any alphanumeric suffixes.	AC DRIVE
<b>T5-T8</b> , Models IS580, followed by T, followed by 020, 030, 035, 040, 050, 070, 080, 100, 140, 170 or 210, followed by -R1, -R2, or -D, followed by -P1, may be followed by any alphanumeric suffixes.	AC DRIVE
<b>T5-T8</b> , Models MD290, followed by T, followed by 18.5, 22, 30, 37, 45, 55, 75, 90, 110 or 132, followed by G, followed by /, followed by 22, 30, 37, 45, 55, 75, 90, 110 or 132, followed by P, followed by B or null, followed by - P1, may be followed by any alphanumeric suffixes.	AC DRIVE
<b>T5-T8</b> , Models MD500, MD500E, followed by T, followed by 18.5, 22, 30, 37, 45, 55, 75, 90, 110 and 132, followed by P or G, may be followed by B or null, followed by -P1, may be followed by any alphanumeric suffixes.	AC DRIVE
<b>MD520</b> , Open type MD520, followed by -4T, followed by 18.5, 22, 30, 37, 45, 55, 75, 90 and 110, followed by B or null, followed by S or null, followed by -T or null, followed by null, may be followed by any alphanumeric suffixes.	Power Conversion Equipment
Open type, Models CS200,, CS710 followed by -4T, followed by 18.5, 22, 30, 37, 45, 55, 75, 90 and 110, followed by G, may be followed by B or null, may be followed by any alphanumeric suffixes.	Power Conversion Equipment
Open type, Models MD290,, followed by T, followed by 18.5, 22, 30, 37, 45, 55, 75, 90, 110 or 132, followed by G, followed by /, followed by 22, 30, 37, 45, 55, 75, 90, 110 or 132, followed by P, followed by B or null, may be followed by any alphanumeric suffixes.	Power Conversion Equipment
Open type, Models MD500,, MD500E, followed by T, followed by 18.5, 22, 30, 37, 45, 55, 75, 90, 110 and 132, followed by P or G, may be followed by B or null, may be followed by any alphanumeric suffixes.	Power Conversion Equipment

Bamely

Bruce Mahrenholz, Director North American Certification Program

UL LLC

Certificate Number Report Reference Date

UL-CA-L467465-411-13704102-3 E467465-20140731 26-Oct-2022

Open type, Models IS580,, followed by T, followed by 020, 030, 035, 040, 050, 070, 080, 100, 140, 170 or 210, followed by -R1, -R2, or -D, may be followed by any	Power Conversion Equipment
alphanumeric suffixes.	$\times$ $\times$ $\times$ $\times$ $\times$



Bruce Mahrenholz, Director North American Certification Program

UL LLC

